

Smart Mobile POS Payment Terminal MP-200

The MP-200 is the cutting-edge secure electronic terminal powered by safe-Android 7.0 operation system. It comes with a 5.5inch high definition colorful display, industrial level thermal printer and flexible configuration for various barcode scanner scenarios. A wide range of advanced connectivity options are supported for global 3G/4G network, as well as inbuilt NFC contactless, BT4.0 and WIFI.



Empowered by Quad-core CPU and massive memory, MP-200 enables exceptionally fast processing of applications, and supports additional features for local customization including fingerprint reader module.



CHAMPTEK[°]

Features

- Android 7.0 OS;
- 5.5 inch TFT IPS LCD, resolution 1280*720;
- · Built-in high speed thermal printer , with over 50Km print life
- Full bands for global coverage: 4G/3G/2G,WLAN,VPN
- Crossmatch, 508dpi fingerprint module for biometric identification
- Dual camera for quickly QR code scan & 2D scanner as option


Specifications

Basic Characteristics Radio Communication	OS	Safe OS based on Android 7.0
	CPU	Quad-Core 1.35GHZ
	ROM	8GB ROM EMMC
	RAM	1G RAM LPDDR3
	Display	5.5 inch TFT IPS LCD, resolution 1280*720
	Panel	Ultra-sensitive capacitive touch screen, can work with gloves and wet fingers
	Dimensions	206mmX84mmX32mm (max 56mm)
	Weight	530g(Battery included)
	Keys	3 Physical keys:1 ON/OFF KEY,2 Shortcut keys 3 Virtual keys: Menu, Home, Back
	Input	Chinese/English ,and supports handwriting and soft keyboard
	WIFI	IEEE 802.11 a/b/g/n ,support dual Band 2.4GHZ and 5GHZ
	Bluetooth	BT 4.0 LE +EDR
	4G	TD-LTE:Band38, Band39, Band40, Band41 FDD- LTE:Band1,Band3,Band7,Band8,Band20
	3G	UMTS(WCDMA)/HSPA+:Band1,Band8,Band2,Band5 TD- SCDMA:Band34,Band39
	2G	GSM/GPRS/EDGE:850/900/1800/1900MHZ
Card Reader	Magnetic card reader (Optional)	Supports ISO7811/7812/7813, and supports triple track (tracks 1/2/3), bi-directional
	Smart Card reader (Optional)	Supports ISO7816 standard
	Contactless Card reader	Supports 14443A / 14443B, all other NFC cards
Expansion and Peripheral	Printer	High-Speed Thermal Printer ; 58mm printing paper ; 40mm paper roll



	Camera	5MP camera with LED flash and auto-focus function
	Satellite Positioning	GPS, Supports A-GPS
	Audio	Speaker ,Microphone, Earphone
Interfaces	Micro SD Card Slot	1 PCS
	SIM Card Slot	2 PCS MICRO SIM
	PSAM Card Slot	2 PCS Conforms to ISO7816 standard
	USB Port	1PCS TYPE C USB
Power	Battery	Li-ion battery ,7.4V /2600mAH
	Charging Port	Type C USB Port ,5V DC,2A
Environment	Operating Temperature	-10°C to 50°C
	Storage Temperature	-20°C to 70°C
	Humidity	5% to 95% Relative Humidity, Non-Condensing
Certification	Electromagnetic	CE, Rohs, FCC, BIS
	Fingerprint	STQC/FBI
Optional	Fingerprint	Semiconductor capacitance 18mm x 12.8mm imaging area 256 x 360 pixel array, Crossmatch FBI certified 508dpi
	Front camera	2 Megapixel Fixed Focal Camera
	Barcode Scanner	Symbol 4710 2D Image Engine, Support 1D and 2D symbologies
	Positioning	GLONASS, Bei-Dou satellite navigation system

One device, all payments.





CHAMPTEK INCORPORATED

1F, No.4, Alley 2, Shih-Wei Lane, Chung-Cheng Rd., Xindian District, New Taipei City 23162,Taiwan sales@champtek.com

Disclaimer: This product specification is subject to change without prior notice.

www.champtek.com

Smart & Reliable