


CASTOR C-5010

CASTOR C-5010



Introduction

The flattest horizontal scan solution!

The CASTOR is the high-performance food retail bar code scanner and the pearl under the horizontal scanners. Designed from a quality point of view, the CASTOR comes with a stainless steel top deck to ensure a long lifetime and with a metal housing.

The CASTOR is well protected against harmful interference from the moving belt's motor and against electrical static discharge from the operator.

With real vertical scan lines, the need to lift and tilt a product being scanned has disappeared and operator fatigue is reduced. Consequently, checkout efficiency increases.

Like all other Scantech scanners, the CASTOR is optimised for EAS integration and is compatible with today's market solutions.

CASTOR C-5010

Features

- Flattest and most rugged retail bar code scanner optimized for horizontal scanning.
- Height is only 75 mm which ensures a flexible and ergonomic installation under all circumstances.
- Dense 5 – field, 15 lines scan pattern and scan rate of 1500 scans/second guarantees an excellent omni – directional bar code reading.
- No need to lift and tilt a product due to the real vertical scan lines.
- The Scantech ID STAR code reconstruction software allows easy reading of truncated, damaged and substandard bar codes.
- Standard auxiliary port for connecting other scanners. For example a hand held scanner to scan heavy or voluminous products.
- EAS compatible.

Specifications

Physical Characteristics

Depth	75 mm
Width	205 mm
Length	240 mm
Weight	2.5 kg
Cable	Straight 5 ft.

Electrical

Power Supply Voltage 100-240 V ac, 50/60 Hz

DC input to scanner DC +12 V

Interfaces

RS232, USB (USB HID, Virtual COM port), Keyboard Wedge, Powered USB

Scanner Characteristics

Light source 650 ± 10nm VLD

Depth of field 150 mm@EAN 0.33mm/13mil PCS@90%

Scan pattern 5 direction scan field, 15 lines scan pattern

Scan rate 1500 scans per second

Barcode types GS1 DataBar, EAN/UPC/JAN including Add – On, Code 128, EAN128, Code 39, Code 32, Codabar, Interleaved 2/5

Compatibility

EAS compatible

Environmental

Operating Temp 0°C – 40°C

Humidity Relative humidity to 95% (non – condensing)

Safety

Laser Safety IEC 825 – 1 (1993) Class I, U.S. 21CFR1040 Class IIa

Electrical Safety EN 60950 (second edition) UL1950 (third edition), c – UL (according CSA22.2.950)

Radio and TV Interference EN55022 Class B (1994), FCC part 15 Class A (1992)

Radio Frequency Immunity EN 50082 – 1 (1992)

Harmonic Current Emissions EN 61000 – 3 – 2 (1995)

Regularity of Compliance

CE, FCC and RoHs compliant 



Due to Champtek's / Scantech ID's continuing product improvement programs, specifications and features are subject to change without notice.